



ISO-9001 Registered Quality System.
ISO-21469 Compliant.

Sales, Service & Distribution Center

Newark, NJ 07105
Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center

Toledo, OH 43605
Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support

Phone: 1-800-733-4755

PRODUCT DATA

LUBRIPLATE VACUUM PUMP OILS

DESCRIPTION

LUBRIPLATE VACUUM PUMP OILS are high performance, non-detergent mineral oils. They possess exceptional flash and fire points, as well as high V.I.'s (Viscosity Index).

APPLICATIONS

LUBRIPLATE VACUUM PUMP OIL is recommended for most rotary vane and rotary lobe vacuum pumps. It is designed to alleviate the sludge, carbon deposit and contamination problems commonly found in industrial vacuum pumps.

LUBRIPLATE VACUUM PUMP OIL LIGHT is recommended for rotary vane vacuum pumps typically associated with delicate instrumentation. These vacuum pumps generally have a drip oiler involved. The use of this oil will provide for optimum lubrication without the formation of carbon deposits.

ADVANTAGES

⇒ No additives such as rust inhibitors

Typical Test Data

PROPERTY	TEST METHOD	TYPICAL RESULTS*	
		Vacuum Pump Oil Light	Vacuum Pump Oil
Viscosity: SUS @ 210°F	ASTM D-2161	47	67
SUS @ 100°F	ASTM D-2161	180	505
cSt @ 100°C	ASTM D-445	6	12
cSt @ 40°C	ASTM D-445	34	97
Viscosity Index	ASTM D-2270	122	109
API Gravity	ASTM D-287	31.5	30.1
Flash Point °F/°C	ASTM D-92	425°F/219°C	485°F/252°C
Fire Point °F/°C	ASTM D-92	440°F/227°C	530°F/277°C
Pour Point °F/°C	ASTM D-97	-35°F/-37°C	-5°F/-21°C
ISO VG	ASTM D-2422	32	100

PACKAGING AVAILABLE

Carton, 12/1 Quarts
Carton, 4/1 Gallon Jugs
5 Gallon Pail
55 Gallon Drum

VACUUM OIL LIGHT

L0944-054
L0944-057
L0944-060
L0944-062

PACKAGING AVAILABLE

Carton, 12/1 Quarts
Carton, 4/1 Gallon Jugs
5 Gallon Pail
55 Gallon Drum

VACUUM PUMP OIL

L0945-054
L0945-057
L0945-060
L0945-062