



ISO-9001 Registered Quality System.
ISO-21469 Compliant.

Sales, Service & Distribution Center
Newark, NJ 07105
Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center
Toledo, OH 43605
Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support
Phone: 1-800-733-4755

PRODUCT DATA

LUBRIPLATE STO-FG

"This product is certified OU Kosher Pareve"
"This product is Halal certified"

*NSF International H-1 Registered
NSF ISO21469 Certification

DESCRIPTION

LUBRIPLATE STO-FG is a special, compounded oil recommended for the lubrication of stirrups on bottle filling machines.

APPLICATIONS

⇒ Stirrups – Bottle Fillers

ADVANTAGES

LUBRIPLATE STO-FG has excellent emulsifying properties to provide a lubricating film on the metal surfaces even in the presence of excessive moisture. LUBRIPLATE STO-FG is also compounded with dispersant type additives to keep the metal surfaces from building up with undesirable residues. This anti-wear oil is designed for areas of "incidental contact" requiring an NSF International H-1 registered product.

STORAGE RECOMMENDATIONS

1. Products should be stored between 40°F-120°F.
2. Products should be stored in a dry covered environment.
3. Products should not be stored in warm, direct sunlight.
4. Improper storage conditions can significantly alter the shelf life of the product. Such conditions would include temperature, moisture, open containers, etc.

Typical Test Data

PROPERTY	TEST METHOD	TYPICAL RESULTS*
Viscosity SUS @ 100°F	ASTM D-2161	350
Viscosity cSt @ 40°C	ASTM D-445	67
ISO		68
SAE Viscosity		20
API Gravity	ASTM D-287	29.0
Color	ASTM D-1500	0.0
Flash Point °F/°C	ASTM D-92	425°F/219°C
Fire Point °F/°C	ASTM D-92	485°F/252°C
Pour Point °F/°C	ASTM D-97	-15°F/-26°C
Four Ball Wear Test	ASTM D-2266	.36 mm

PACKAGING AVAILABLE

Part No.

5 Gallon Pail

L0863-060

55 Gallon Drum

L0863-062

***NSF International H-1 Registration No.**
(Meets former USDA 1998 Guidelines)

126120

**Registered H-1 by NSF International for use in food processing facilities as a lubricant or anti-rust agent on equipment in which there may be incidental contact involving the lubricated part and the edible product.*

"LUBRIPLATE STO-FG contains no components derived from TSE/BSE relevant animal species; therefore, it is compliant with the requirements of the TSE Note for Guidance EMA/410/01 Rev. 3 July 2011."



Nonfood Compounds
H1 Registered
ISO 21469 Certified

PAREVE

HALAL