



ISO-9001 Registered Quality System.
ISO-21469 Compliant.

Sales, Service & Distribution Center

Newark, NJ 07105
Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center

Toledo, OH 43605
Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support

Phone: 1-800-733-4755

PRODUCT DATA

LUBRIPLATE UTF

DESCRIPTION

LUBRIPLATE UTF is a high quality, specially designed lubricant containing anti-rust, anti-foam and oxidation inhibitors; plus, other additives necessary for the wide range of applications recommended by various tractor manufacturers. The product is an "all-seasonal" type of oil that resists thickening in cold weather and thinning in the heat of the summer. It is compounded with detergents to keep transmissions clean and maintain hydraulic control circuits in perfect working condition; and provides excellent protection against seal and pump deterioration.

RECOMMENDATIONS

LUBRIPLATE UTF is recommended for use in equipment made by:

- ⇒ **Allison** - Hydraulic Trans Fluid; GMC, Type C, C-1, C-2, C-3, C-4
- ⇒ **Allis-Chalmers** - #272843, Part #924282 (Power Fluid No. 821), Part #246634
- ⇒ **Caterpillar** - TO-2
- ⇒ **Clark Transmissions**
- ⇒ **Duetz-Allis** - 272843 (Power Fluid 821XL)
- ⇒ **J. I. Case** - Hi-Lo CH Fluid JIC 145, Case-O-Matic Type A, JIC 143, JIC 144, JIC-C-185 (TFD), MS-1205 (TFD-II), MS-1206 (Powerguard PTF), MS-1207 (Hy-Trans-Plus), MS-120 1, MS-1209 (Hy-Tran ULTRA)
- ⇒ **Case New Holland**- MAT 3505, MAT 3525, MAT 3526
- ⇒ **Ford New Holland** - M-2C41 Selecto-Speed Fluid, ESN M-2-C41A, M-2C41-B, M-4864A, M-2C65A, M-2C77A, M-4864B, M-2C65B, M-2C78A, M-2C86A, M-2C134B, M-2C134D, FNHA-2-C-200 & 201
- ⇒ **Fiat Hesston** - AF-87
- ⇒ **International Harvester** - Hy-trans Fluid, (B-5, B-6, B-7)
- ⇒ **John Deere** - Fluid Type 303 (J-14C), Part #AR-284254, Part #AR-269444, J-14B, J-20A, J-20B (Hy-Guard), J-20C, Quatrol Requirements, J21A, J20D
- ⇒ **Kubota** - UDT Fluid
- ⇒ **Landini**
- ⇒ **Massey Ferguson** - M-1103A, M-1103B, M-1110, M-129A, M1135, Permatron III, M-1141
- ⇒ **Oliver** - Where additive Part #102082A is mixed with 10W, 5W20, 10W30 oil; in 1 part to 16 parts oil, Type 55 and Renk 874 A/B transmission
- ⇒ **White** - Universal Fluid
- ⇒ **Stieger** - Hydraulic Trans Fluid, Gear, Hydraulic and Wet Brake Oil
- ⇒ **Sundstrand** - Pumps
- ⇒ **Versatile** - Specs 23M or 24M
- ⇒ **White Farm** - Hydraulic Oil Type 55 Fluid, White Universal Fluid, White Farm Q-1760, Q-17668, White UTHF, Q-1826

Typical Test Data

PROPERTY	TEST METHOD	TYPICAL RESULTS*
SAE Grade		10W20
API Gravity	ASTM D-287	28.4
Viscosity cSt @ 40°C	ASTM D-445	58.9
Viscosity cSt @ 100°C	ASTM D-445	8.7
Viscosity Index	ASTM D-2270	133
Brookfield Vis @ -18°C, cP		4,000 max
Brookfield Vis @ -34°C, cP		70,000 max
Pour Point, (°F)	ASTM D-5950	-35

ADVANTAGES

- ⇒ Excellent gear, bearing and pump wear protection
- ⇒ Multi-functional fluid
- ⇒ Oxidation and thermal stability for long life
- ⇒ Excellent rust and corrosion protection
- ⇒ Reduces brake chatter
- ⇒ Compatibility with oil seal materials used in transmission and hydraulic systems

APPLICATIONS

Operators, especially farmers, will appreciate the multipurpose application for transmissions, final drives, and hydraulic systems of tractors thereby eliminating the need for additional oil products.

PACKAGING AVAILABLE

Case, 4/1 Gallon Jugs
5 Gallon Pail
16 Gallon Drum
55 Gallon Drum

Part No.

L0873-057
L0873-060
L0873-061
L0873-062