



ISO-9001 Registered Quality System.  
ISO-21469 Compliant.

**Sales, Service & Distribution Center**

Newark, NJ 07105  
Phone: 973-589-9150 Fax: 973-589-4432

**Manufacturing, Sales, Service & Distribution Center**

Toledo, OH 43605  
Phone: 419-691-2491 Fax: 419-693-3806

**Sales and Tech Service Support**

Phone: 1-800-733-4755

**PRODUCT DATA**

**LUBRIPLATE SUPER GPO 40 MOTOR OIL**

**DESCRIPTION**

**Meets or exceeds the following specifications:**

- ⇒ API CF-2
- ⇒ API CF (obsolete)
- ⇒ MIL-PRF-2104G
- ⇒ Detroit Diesel 2-stroke cycle engines, Oil Type 1 (1.0 % max. Sulfated ash)
- ⇒ Arvin Meritor, Dana Spicer and Eaton Fuller manual transmissions

**APPLICATIONS**

LUBRIPLATE Super GPO 40 Motor Oil is a high-quality diesel engine oil designed for use in a wide variety of applications, including off-highway diesel equipment, farm machinery, marine engines, 2-stroke cycle diesel engines (in the appropriate viscosity grades) and mixed commercial fleets. It may be also used in some heavy duty manual transmissions in trucks and busses.

**ADVANTAGES**

- ⇒ Excellent soot control for protection against abrasive wear and soot-induced oil thickening
- ⇒ Protects against sludge and varnish formation
- ⇒ Protects against scuffing and wear
- ⇒ Protects against rust and bearing corrosion
- ⇒ Good resistance to foaming and aeration
- ⇒ Low-ash content to minimize the formation of ash deposits and helps keep intake ports clean

**Typical Test Data**

PROPERTY	TEST METHOD	TYPICAL RESULTS*
Viscosity cSt @ 40°C	ASTM D-445	149
Viscosity cSt @ 100°C	ASTM D-445	15.4
SAE Grade		40
Viscosity Index	ASTM D-2270	106
Pour Point °F	ASTM D-5950	-27
TBN (min)	ASTM D-2896	8.1
Zinc, wt %	ASTM D 5185	0.109
Sulfated Ash % wt	ASTM D-874	1.0

**PACKAGING AVAILABLE**

5 Gallon Pail  
55 Gallon Drum

**Part No.**

L0752-060  
L0752-062