



ISO-9001 Registered Quality System.  
ISO-21469 Compliant.

**Sales, Service & Distribution Center**

Newark, NJ 07105  
Phone: 973-589-9150 Fax: 973-589-4432

**Manufacturing, Sales, Service & Distribution Center**

Toledo, OH 43605  
Phone: 419-691-2491 Fax: 419-693-3806

**Sales and Tech Service Support**

Phone: 1-800-733-4755

**PRODUCT DATA**

**LUBRIPLATE SUPER HDS 30 MOTOR OIL**

**DESCRIPTION**

LUBRIPLATE Super HDS 30 Motor Oil is premium quality engine oil for all-season use in commercial mixed-fleet engine operations. LUBRIPLATE Super HDS 30 Motor Oil is manufactured to meet the performance requirements in all naturally aspirated, turbocharged and supercharged diesel engines as well as all four-cycle gasoline engines.

**Meets or exceeds the following specifications:**

- ⇨ API CF-2
- ⇨ API CF
- ⇨ API CE (obsolete)
- ⇨ API CD-II (obsolete)
- ⇨ API CD
- ⇨ API SJ
- ⇨ API SH
- ⇨ MIL-L-2104F
- ⇨ MIL-L-46152D

**APPLICATIONS**

LUBRIPLATE Super HDS 30 Motor Oil is recommended for all major automotive diesel and mixed fleet (diesel/four cycle gasoline engines) operations in all service and under all operating conditions where the equipment owner specifies the use of single grade engine oils.

**ADVANTAGES**

- ⇨ Resisted breakdown under high temperatures
- ⇨ Maintained oil pressure under heavy load conditions
- ⇨ Minimized rust and corrosion
- ⇨ Good low temperature pour point

**Typical Test Data**

PROPERTY	TEST METHOD	TYPICAL RESULTS*
Viscosity cSt @ 40°C	ASTM D-445	93
Viscosity cSt @ 100°C	ASTM D-445	11.8
SAE Grade		30
Viscosity Index	ASTM D-2270	100
Sulfated Ash % wt	ASTM D-874	<1.0
Pour Point, °F	ASTM D-5950	-27
TBN (min)	ASTM D-2896	7.5

**PACKAGING AVAILABLE**

Carton, 12/1 Quart Plastic Bottles  
55 Gallon Drum

**Part No.**

L0791-054  
L0791-062