



ISO-9001 Registered Quality System.  
ISO-21469 Compliant.

**Sales, Service & Distribution Center**  
Newark, NJ 07105  
Phone: 973-589-9150 Fax: 973-589-4432

**Manufacturing, Sales, Service & Distribution Center**  
Toledo, OH 43605  
Phone: 419-691-2491 Fax: 419-693-3806

**Sales and Tech Service Support**  
Phone: 1-800-733-4755

## PRODUCT DATA

# LUBRIPLATE NEPTUNE LAUNCHING SLIP COAT

### DESCRIPTION

LUBRIPLATE Neptune Launching Slip Coat is to be applied over the hardened Base Coat layer. LUBRIPLATE Neptune Launching Slip Coat is extremely water resistant and can be used over a wide temperature range.

### APPLICATION

LUBRIPLATE Neptune Launching Slip Coat is applied from the drum as is. It should not be heated prior to application. After the LUBRIPLATE Neptune Launching Base Coat has cooled, the Slip Coat is spread on to the desired thickness. Typical thickness is 1/4" to 1/2". LUBRIPLATE Neptune Launching Slip Coat is orange in color making it distinguishable from the LUBRIPLATE Neptune Launching Base Coat.

### Typical Test Data

PROPERTY	TEST METHOD	TYPICAL RESULTS
NLGI No.		3 1/2
<b>Penetration Range:</b>	ASTM D-217	
60 Strokes Worked		210 - 250
Thickener		Calcium Soap
Dropping Point	ASTM D-566	200°F
Specific Gravity	ASTM D-4052	0.93
Color	Visual	Orange
Texture	Visual	Smooth

### PACKAGING AVAILABLE

400 lb. Drums

### Part No.

L0215-040

### COVERAGE

Thickness in Inches	Pounds Required to Cover 1 Square Foot (Approx.)	Drum (About 325 lbs.) Will Cover Square Feet (Approx.)
1/8	.60	666
1/4	1.20	333
1/2	2.37	169