



ISO-9001 Registered Quality System.
ISO-21469 Compliant.

Sales, Service & Distribution Center
Newark, NJ 07105
Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center
Toledo, OH 43605
Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support
Phone: 1-800-733-4755

PRODUCT DATA

LUBRIPLATE SYN FG DRILL & TAP

"This product is certified OU Kosher Pareve"
"This product is Halal certified"

*NSF International H-1 Registered
NSF ISO21469 Certification

DESCRIPTION

LUBRIPLATE Synthetic Food Grade Drilling & Tapping Fluid is a full synthetic fluid designed specifically for drilling & tapping. This product is NSF H1 Registered making it ideal for food processors, food package manufacturers and the pharmaceutical industry.

APPLICATIONS

- ⇒ Drilling and Tapping

ADVANTAGES

- ⇒ NSF H1 Registered Food Grade
- ⇒ Non-Toxic
- ⇒ Excellent performance on stainless steel, steel, and aluminum
- ⇒ Does not contain sulfur, chlorine, or mineral oil
- ⇒ Provides minimal smoke

STORAGE RECOMMENDATIONS

- ⇒ Products should be stored between 40°F-120°F
- ⇒ Products should be stored in a dry covered environment
- ⇒ Products should not be stored in warm, direct sunlight
- ⇒ Improper storage conditions can significantly alter the shelf life of the product. Such conditions would include temperature, moisture, open containers, etc.

Typical Test Data

| PROPERTY | TEST METHOD | TYPICAL RESULTS* |
|-------------------|-------------|-------------------|
| Consistency | | Liquid |
| Odor | | None |
| Viscosity: | | |
| SUS @ 100°F | ASTM D-2161 | 112 |
| cSt @ 40°C | ASTM D-445 | 21 |
| SUS @ 210°F | ASTM D-2161 | 31 |
| cSt @ 100°C | ASTM D-445 | 5 |
| Viscosity Index | ASTM D-2270 | 141 |
| API Gravity | ASTM D-287 | 18.7 |
| Specific Gravity | ASTM D-1298 | 0.94 |
| Flash Point | ASTM D-92 | >480°F/ >249°C |
| Color | ASTM D-1500 | <1.5 |
| Color APHA | ISO 2211 | 75 |

PACKAGING AVAILABLE PART NUMBER

| | |
|---------------------------|-----------|
| Case of 12 4 oz. bottles | L0540-014 |
| Case of 12 8 oz. bottles | L0540-018 |
| Case of 12 16 oz. bottles | L0540-026 |
| Case of 12 1 qt. bottles | L0540-054 |
| Case of 4 1 gal. jugs | L0540-057 |
| 5 Gallon pail | L0540-060 |
| 55 Gallon Drum | L0540-062 |
| Case of 12 8 oz. bottles | L0540-018 |

*NSF International H-1 Registration No.'s
(Meets former USDA 1998 Guidelines)

163171

*Registered H-1 by NSF International for use in food processing facilities as a lubricant or anti-rust agent on equipment in which there may be incidental contact involving the lubricated part and the edible product.

"LUBRIPLATE SYNTHETIC FOOD GRADE DRILLING & TAPPING FLUID contains no components derived from TSE/BSE relevant animal species; therefore, it is compliant with the requirements of the TSE Note for Guidance EMA/410/01 Rev. 3 July 2011".



Nonfood Compounds
H1 Registered
ISO 21469 Certified



PAREVE



HALAL