



ISO-9001 Registered Quality System.  
ISO-21469 Compliant.

**Sales, Service & Distribution Center**  
Newark, NJ 07105  
Phone: 973-589-9150 Fax: 973-589-4432

**Manufacturing, Sales, Service & Distribution Center**  
Toledo, OH 43605  
Phone: 419-691-2491 Fax: 419-693-3806

**Sales and Tech Service Support**  
Phone: 1-800-733-4755

## PRODUCT DATA

# LUBRIPLATE SYNXTREME HT MAX PLUS

“This product is certified OU Kosher Pareve”  
“This product is Halal certified”

\*NSF International H-1 Registered  
NSF ISO21469 Certification

## DESCRIPTION

LUBRIPLATE SYNXTREME HT MAX PLUS is a completely fluorinated synthetic lubricant specially formulated to provide effective long-term lubrication to equipment exposed to temperatures in excess of 260°C.

## ADVANTAGES

- ⇒ Excellent Thermo-Oxidative Stability
- ⇒ Low Volatility
- ⇒ Excellent Compatibility with Plastics and Elastomers
- ⇒ Chemically Inert Towards Chemicals & Fuels
- ⇒ Non-Flammable
- ⇒ Non-Melting Thickeners

## SAFETY

LUBRIPLATE SYNXTREME HT MAX PLUS does not contain hazardous ingredients. If fumes are generated at elevated temperatures, ventilation is required. See the Safety Data Sheet for additional safety related information on this lubricant.

## STORAGE RECOMMENDATIONS

- ⇒ Products should be stored between 40°F-120°F
- ⇒ Products should be stored in a dry covered environment
- ⇒ Products should not be stored in warm, direct sunlight
- ⇒ Improper storage conditions can significantly alter the shelf life of the product. Such conditions would include temperature, moisture, open containers, etc.

## Typical Test Data

PROPERTY	TEST METHOD	TYPICAL RESULTS*
Base Fluid Type	Report	PFPE
Color	Visual	White
Unworked Penetration	ASTM D217	294
Particle Size	Hegman	<5µm
Evaporation, 24h @ 100°C	CTM-1	0.01%
TGA Temp. @ 5% Weight Loss	ASTM D972	448°C
Oil Separation, 24h @ 100°C	ASTM D6184	7.50%

## SPECIFICATIONS

The typical properties reported on this technical data sheet should not be used for preparing specifications on this lubricant. Please contact LUBRIPLATE for assistance in preparing a specification.

## PACKAGING AVAILABLE

Carton – 1 28 oz. Cartridge  
60 lb. Pail  
450 lb. Drum

## Part No.

L0332-002  
L0332-035  
L0332-040

**\*NSF International H-1 Registration No.**  
(Meets former USDA 1998 Guidelines)

**165324**

\*Registered H-1 by NSF International for use in food processing facilities as a lubricant or anti-rust agent on equipment in which there may be incidental contact involving the lubricated part and the edible product.

“LUBRIPLATE SYNXTREME HT MAX PLUS contains no components derived from TSE/BSE relevant animal species; therefore, it is compliant with the requirements of the TSE Note for Guidance EMA/410/01 Rev. 3 July 2011.”

Manufactured with ingredients that comply with FDA 21 CFR 178.357.

