



Introducing A New Food Grade Lubricant

Safe enough for applications where direct contact with food is possible.

Lubriplate® **3H DIRECT** FOOD MACHINERY LUBRICANT

Formulated from Pure USP White Mineral Oil, Lubriplate 3H Direct is NSF 3H & H1 Registered for use as a lubricant or release agent on food processing equipment where direct contact with food is possible.

| SPECIFICATIONS | |
|---------------------------------|-----------------------|
| NSF CATEGORY CODES | 3H & H1 |
| NSF REGISTRATION NUMBER | 158254 |
| NLGI GRADE (ASTM D-217) | 2 |
| DROPPING POINT (ASTM D-2265) | >500°F / >260°C |
| BASE OIL | USP WHITE MINERAL OIL |
| BASE OIL VISCOSITY cSt @ 40°C | 75 |
| PACKAGE 14 OZ / 397 g CARTRIDGE | PART No. L0174-002 |



Lubriplate®
Lubricants

Backed By: **Lubriplate® ESP**

Complimentary Extra Services Package

Plant Surveys / Tech Support / Training
Color Coded Lube Charts & Machine Tags
Lubrication Software / Follow-Up Oil Analysis

Newark, NJ 07105 / Toledo, OH 43605 / 800-733-4755
LubeXpert@lubriplate.com / www.lubriplate.com



The Best Food Machinery Lubricants Also Come In Small Convenient Packages.



SYNXTREME FG-1 & FG-2

NSF H1, High Performance, Extreme Pressure, High Temp, Synthetic, Calcium Sulfonate Complex Greases.

SYNXTREME FG-1 (NLGI No. 1)
CARTRIDGES 15.5 OZ. (440 g)
Part No. L0306-098

SYNXTREME FG-2 (NLGI No. 2)
CARTRIDGES 16 OZ. (454 g)
Part No. L0305-098



SFL-1 & SFL-2

NSF H1, Synthetic, High Performance, Aluminum Complex Type Greases For High / Low Temperature Applications.

SFL-1 (NLGI No. 1)
CARTRIDGES 13.5 OZ. (383 g)
Part No. L0197-098

SFL-2 (NLGI No. 2)
CARTRIDGES 13.5 OZ. (383 g)
Part No. L0198-098



FGL-0, FGL-1 & FGL-2

NSF H1, USP Mineral Oil-Based, Super Multi-Purpose, Aluminum Complex Greases.

FGL-0 (NLGI No. 0)
CARTRIDGES 13 OZ. (369 g)
Part No. L0230-002

FGL-1 (NLGI No. 1)
CARTRIDGES 14 OZ. (397 g)
Part No. L0231-098

FGL-2 (NLGI No. 2)
CARTRIDGES 14 OZ. (397 g)
Part No. L0232-098



SYNXTREME HT MAX

NSF H1 Registered, Ultra High-Temperature Perfluoropolyether PFPE-Based Grease.

SYNXTREME FG-2 (NLGI No. 2)
CARTRIDGES 28 OZ. (794 g)
Part No. L0331-002



PURE TAC & PURE TAC LIGHT

NSF H1, Tacky, Adhesive, USP Mineral Oil-Based, Aluminum Complex Greases. Excellent For Open Gears.

PURE TAC LIGHT (NLGI No. 1.5)
CARTRIDGES 13.5 OZ. (383 g)
Part No. L0235-098

PURE TAC (NLGI No. 2)
CARTRIDGES 14 OZ. (397 g)
Part No. L0236-098



CLEARPLEX, 1 & 2

NSF H1, Clear/Transparent, USP Mineral Oil-Based, Aluminum Complex Greases.

CLEARPLEX TUBE (NLGI No. 1)
TUBES 4 OZ. (113 g)
Part No. L0353-082

CLEARPLEX-1 (NLGI No. 1)
CARTRIDGES 13 OZ. (369 g)
Part No. L0350-098

CLEARPLEX-2 (NLGI No. 2)
CARTRIDGES 13 OZ. (369 g)
Part No. L0351-098



SYNXTREME FG-2 Spray

NSF H1, High Performance, Extreme Pressure, High Temp, Synthetic, Calcium Sulfonate Complex Spray Grease.

SYNXTREME FG-1 Spray
11 OZ. (312 g)
Part No. L0305-063



SFGO Ultra-7 Spray

NSF H1, Synthetic, Multi-Purpose, Chain and Penetrating Fluid.

SFGO ULTRA-7 Spray
11 OZ. (312 g)
Part No. L0912-063



FGL-1 Spray

NSF H1, Anti-Wear Fortified, Multi-Purpose, Spray Grease Type Lubricant.

FGL-1 Spray
11 OZ. (312 g)
Part No. L0231-063



FMO-350AW Spray

NSF H1 Registered, Anti-Wear Fortified, Multi-Purpose, Spray Lubricating Oil.

FMO-350 AW Spray
12 OZ. (340 g)
Part No. L0882-063



Food Grade Silicone Lubricant

NSF H1 Registered, General-Purpose, Silicone Spray Lubricant.

Food Grade Silicone Lubricant
9.5 OZ. (269 g)
Part No. L0723-063



FMO-85AW Spray

NSF H1, Anti-Wear Fortified, Multi-Purpose, Non-Aerosol, Hand Pump Spray Lubricating Oil.

FMO-85 AW Pump Spray
14 FL OZ (414 ml)
Part No. L0880-067

Lubriplate® Lubricants

Newark, NJ 07105 / Toledo, OH 43605 / 800-733-4755 / www.lubriplate.com / LubeXpert@lubriplate.com