

Lubriplate®

Fall 2020



Lubri-Topics

Discover What's New At Lubriplate Lubricants



Introducing Lubriplate® 3H Direct Food Grade Lubricant.

Safe enough for applications where direct contact with food is possible.

LUBRIPLATE 3H DIRECT is LUBRIPLATE's first NSF / 3H registered grease. It is formulated from USP ingredients to provide food producers with a grease that is safe for direct contact. It should be used as a release agent for grills, ovens, loaf pans, boning benches, chopping boards or other hard surfaces in contact with food products to prevent food from adhering during processing. LUBRIPLATE 3H DIRECT is especially effective at providing blade lubrication at start-up prior to food production resulting in extending blade life. It is a suitable product for anti-friction bearings, plain bearings, guides, seals and sliding surfaces.

Additional NSF / 3H registered Lubriplate products in oil form are FMO-45, FMO-85, FMO-200, FMO-350, FMO-500, Pan Divider Oil, Pan Divider Oil Light and Silicone Fluid FG-350.

Lubriplate 3H Direct is also NSF / H1 registered.

LUBRIPLATE 3H DIRECT SPECIFICATIONS

NSF CATEGORY CODES	3H & H1
NSF REGISTRATION NUMBER	158254
NLGI GRADE (ASTM D-217)	2
DROPPING POINT (ASTM D-2265)	>500°F / >260°C
BASE OIL	USP WHITE MINERAL OIL
BASE OIL VISCOSITY cSt @ 40°C	75
PACKAGE 14 OZ / 397 g CARTRIDGE	PART No. L0174-002



3H & H1 REGISTERED



Certified Kosher Pareve



HALAL



ISO 21469 Certified



Lubriplate Lubricants Company

NEWARK, NJ 07105 / TOLEDO, OH 43605 / 800-733-4755
LubeXpert@lubriplate.com / www.lubriplate.com



CELEBRATING

150 YEARS

OF QUALITY, INNOVATION & PERFORMANCE

Introducing: Lubriplate® FP-150 Spray A Classic Product In New Packaging.

Lubriplate FP-150 is now available in a convenient aerosol can. This clear lubricating oil is NSF / H1 registered and is thick, tacky, and dripless and is water and steam resistant. It is a multi-purpose product for numerous general oiling applications at food and beverage processing facilities, especially for proofer chains in baking facilities.

LUBRIPLATE FP-150 SPRAY SPECIFICATIONS	
NSF CATEGORY CODE	H1
NSF REGISTRATION NUMBER	159263
BASE OIL	USP WHITE MINERAL OIL
BASE OIL VISCOSITY cSt @ 40°C	460
PACKAGE 11 OZ / 312 g AEROSOL CAN	PART No. L0735-063



Introducing: SYNXTREME ASAP Lubriplate's New, NSF H1 Registered Food Machinery Grade, Anti-Seize Assembly Paste.

Lubriplate SYNXTREME ASAP is a premium NSF / H1 registered anti-seize compound which protects parts from seizing and rusting together. It is composed of a food-grade, high-heat resistant carrier which is fortified with rust and corrosion inhibitors and antioxidants. This product will not separate, will not drip and will not harden, allowing for easy disassembly and removal of connection even after lengthy service or severe conditions. Lubriplate SYNXTREME ASAP is highly resistant to salt water and is compatible with all types of metals and most plastics. Packaged in 8 oz / 227 g Brush In Cap Can, Part No. L0404-008.

