



FISKE BROTHERS REFINING COMPANY

NEWARK, NEW JERSEY 07105 • TOLEDO, OHIO 43605

FISKE'S EVAP OIL

Description: Colorless, odorless, low viscosity organic lubricating fluid.

Uses: Formulated to meet industry's need for a light duty stamping and forming oil that will evaporate after use, **eliminating the need for a subsequent cleaning operation.** Evap Oil is especially useful for stamping aluminum, galvanized steel, tinplate, copper, brass, terneplate and pre-painted steel.

TYPICAL CHARACTERISTICS:

Viscosity @ 100°F., SUS/cSt	30.5/1.5
Flash Point °F./°C.	130/54
Fire Point °F./°C.	135/57
API Gravity	54.7
Sulfur	No
Active Sulfur	No
Chlorine	No
Fatty Material	No
Color	0.0

Advantages:

- Lubricates like mineral oil
- Non-staining to all metals
- Evaporates within one hour exposure to air
- Does not affect painted surfaces
- No residual odor or oil (Suitable for painting afterward.)
- Safe flash point (130°F.)
- Contains no sulfur or chlorine
- Meets the FDA requirements of a material that may be used as a surface lubricant in the manufacture of metallic articles that contact food

Application: Spray, brush, dip, wipe-on and felt pads.

Caution: This product should be used with adequate ventilation and without frequent bodily contact or prolonged inhalation of vapors. Keep away from flames.

(Over)

Evap Oil is available in the following:

Packaging Available

5 gallon pail
16 gallon drum
55 gallon drum

Part Number

F0524-060
F0524-061
F0524-062