



ISO-9001 Registered Quality System.
ISO-21469 Compliant.

Sales, Service & Distribution Center
Newark, NJ 07105
Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center
Toledo, OH 43605
Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support
Phone: 1-800-733-4755

PRODUCT DATA

LUBRIPLATE WHEEL BEARING GREASE

**DESCRIPTION
&
APPLICATIONS**

LUBRIPLATE Wheel Bearing Grease is a non-corrosive, extreme pressure, water resistant, shear stable lubricant designed for:

All Grease Type Wheel Bearings

- ⇒ Pickups
- ⇒ Cruisers
- ⇒ Heavy Duty Trucks
- ⇒ Highway Truck Trailers
- ⇒ Boat, House & Recreational Trailers
- ⇒ Passenger Cars
- ⇒ Vans
- ⇒ Light & Medium Trucks
- ⇒ Off-Highway Equipment

ADVANTAGES

LUBRIPLATE Wheel Bearing Grease has a high dropping point making it ideal for wheel bearings on vehicles having disc brakes. This lubricant also has a good cold operating temperature making it the “one” wheel bearing lubricant for all temperatures, except the extreme arctic regions.

Typical Test Data

PROPERTY	TEST METHOD	TYPICAL RESULTS*
Thickener		Lithium Complex
Penetration Range	ASTM D-217	265/295
NLGI No.		2
ASTM Dropping Point	ASTM D-566	>500°F/260°C
Worked Penetration: 60 Strokes	ASTM D-217	270
1,000 Strokes	ASTM D-217	273
10,000 Strokes	ASTM D-217	282
100,000 Strokes	ASTM D-217	297
Fluid Viscosity: SUS @ 100°F	ASTM D-2161	1100
cSt @ 40°C	ASTM D-445	215
SUS @ 210°F	ASTM D-2161	92
cSt @ 100°C	ASTM D-445	18
Flash Point	ASTM D-92	500°F/260°C
Fire Point	ASTM D-92	545°F/285°C
Specific Gravity	ASTM D-4052	0.96
Timken E.P. Test: OK Load	ASTM D-2783	60 lb.
Four Ball E.P. Test weld load	ASTM D-2596	680 kg.
Four Ball Wear Test	ASTM D-2266	0.50 mm
Texture	Visual	Tacky
Color	Visual	Off-White

PACKAGING AVAILABLE

Part No.

- | | |
|--------------------------------|-----------|
| Carton, 12/16 oz. Plastic Tubs | L0220-004 |
| Carton, 4/6 lb. Plastic Tubs | L0220-005 |
| 35 lb. Pail | L0220-035 |
| 120 lb. Quarter Size Drum | L0220-039 |
| 420 lb. Full Size Drum | L0220-040 |