



ISO-9001 Registered Quality System.

Sales, Service & Distribution Center
 Newark, NJ 07105
 Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center
 Toledo, OH 43605
 Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support
 Phone: 1-800-733-4755

PRODUCT DATA

LUBRIPLATE “630” SERIES

DESCRIPTION

A series of Lithium-based greases for general purpose lubricants for food processing equipment, as well as industrial applications. With one series of products, inventory and purchasing can be consolidated with LUBRIPLATE “630” greases.

ADVANTAGES

- ⇒ Water resistant
- ⇒ Excellent grease mobility in constant service applications
- ⇒ High anti-wear for extra lubricity
- ⇒ Oxidation inhibited
- ⇒ Wide operating temperature range

APPLICATIONS

LUBRIPLATE No 630-AAA: is an NLGI No. 0 lubricant, is ideal for centralized lubricating systems. Also excellent for certain types of enclosed gear cases (medium speed – no seals) as the lubricant will re-feed itself into the gear train.

LUBRIPLATE No. 630-AA: is an NLGI No. 1 lubricant and the most popular multipurpose general grease. Ideal for automatic dispensing systems, and centralized systems with large lines.

LUBRIPLATE No. 630-A: is a heavy type NLGI No. 2.5 lubricant for applications requiring a cup type lubricant. Excellent for water pumps.

LUBRIPLATE No. 630-2: is an NLGI No. 2 lubricant and the ideal grease gun lubricant for general greasing. LUBRIPLATE No. 630-2 is available in the convenient 14 1/2 oz. grease gun cartridge.

STORAGE RECOMMENDATIONS

- ⇒ Products should be stored between 40°F-120°F
- ⇒ Products should be stored in a dry covered environment
- ⇒ Products should not be stored in warm, direct sunlight
- ⇒ Improper storage conditions can significantly alter the shelf life of the product. Such conditions would include temperature, moisture, open containers, etc.

Typical Test Data

PROPERTY	TEST METHOD	TYPICAL RESULTS			
		630-AAA	630-AA	630-A	630-2
Type of Soap		Lithium	Lithium	Lithium	Lithium
NLGI No.		0	1	2.5	2
Worked Penetration	D-217	355/385	310/340	235/260	265/295
Dropping Point	D-566	360°F 182°C	380°F 193°C	390°F 199°C	380°F 193°C
Viscosity:					
SUS @ 100°F	D-2161	800	750	750	750
cSt @ 40°C	D-445	151	135	135	135
Color	Visual	Off-White	Off-White	Off-White	Off-White

Packaging Available

- Carton, 12/15 oz. Plastic Tubs
- Carton, 4/6 lb. Plastic Tubs
- 35 lb. Pail
- 115 lb. Quarter Size Drum
- 120 lb. Quarter Size Drum
- Full Size Drum
- Carton, 72 - 3/8 oz. Tubes
- Carton, 144/1¼ oz. Tubes (1x6)
- Carton, 36/10 oz. Plastic Tubes

630-AAA

- L0068-004
- L0068-005
- L0068-035
- L0068-039
- ***
- L0068-040
- ***
- ***
- ***

630-AA

- L0067-004
- L0067-005
- L0067-035
- ***
- L0067-039
- L0067-040
- L0067-078
- L0067-086
- L0067-092

Packaging Available

- Carton, 12/15 oz. Plastic Tubs
- Carton, 4/6 lb. Plastic Tubs
- 35 lb. Pail
- 120 lb. Quarter Size Drum
- Full Size Drum
- Carton, 40/14½ oz. Cartridges

630-A

- L0066-004
- L0066-005
- L0066-035
- L0066-039
- L0066-040
- ***

630-2

- L0072-004
- L0072-005
- L0072-035
- L0072-039
- L0072-040
- L0072-098