



ISO-9001 Registered Quality System.
ISO-21469 Compliant.

Sales, Service & Distribution Center
Newark, NJ 07105
Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center
Toledo, OH 43605
Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support
Phone: 1-800-733-4755

PRODUCT DATA

LUBRIPLATE HYDRAULIC OILS
HO-32, HO-46 & HO-68

DESCRIPTION

LUBRIPLATE has developed a complete line of high performance, high and low pressure anti-wear hydraulic oils with excellent oxidation and thermal stability, water tolerance and hydrolytic stability and resistance to yellow metal corrosion. These LUBRIPLATE Hydraulic Oils meet the requirements of:

OEM	SPECIFICATION
Vickers (Eaton)	M-2950-S & I-286-S
General Motors	LS-2
Cincinnati Milacron	P-68, P-69, P-70
Bosch Rexroth	RE 90 220
German Steel Industry	SEB 181222
DIN 51524	Part I & II
AFNOR NF E 48-603	Part I & II
U.S. Steel	No. 126, 127, 136
SAE	MS 1004

APPLICATIONS

These LUBRIPLATE Hydraulic Oils are designed for high performance, anti-wear hydraulic operations. These products minimize the formation of sludge and other corrosive breakdown products which can cause reduction of pump life, filter blocking, and interfere with efficient hydraulic power transfer. This is especially true of Servo valves in modern equipment where the close tolerances between valve assemblies can be hindered by even very low concentrations of sludge. These LUBRIPLATE "HO" Oils are also designed to resist the hydrolyzation of the combination of additives, high operating temperatures and the unavoidable, ever-present, moisture in hydraulic systems which, if not controlled, causes corrosion in phosphor-bronze parts and reduces the anti-wear performance, thus reducing pump life significantly.

ADVANTAGES

- ⇒ High performance anti-wear properties
- ⇒ Oxidation and thermal stability
- ⇒ Excellent filterability in fine filtration systems
- ⇒ Demulsibility
- ⇒ Hydrolytic stability for extended fluid life
- ⇒ Extended pump life
- ⇒ Resistance to yellow metal corrosion.

Typical Test Data

PROPERTY	TEST METHOD	TYPICAL RESULTS*		
		HO-32	HO-46	HO-68
Viscosity: cSt @ 40°C	D-445	34.79	46.34	69.83
cSt @ 100°C	D-445	5.2	6.4	8.2
SUS @ 100°F	D-2161	173	240	328
SUS @ 210°F	D-2161	47	51	55
SAE		10	20	20
ISO		32	46	68
Viscosity Index	D-2270	129	117	106
Flash Point	D-92	440°F/ 227°C	470°F/ 243°C	475°F/ 246°C
Fire Point	D-92	480°F/ 249°C	510°F/ 266°C	510°F/ 266°C
Pour Point	D-97	-40°F/ -40°C	-35°F/ -37°C	-20°F/ -29°C
Gravity	D-287	32.3	32.0	31.8
Color	D-1500	L-1	L-1	L-1.5
Aniline Point 220°F	D-611	220°F	240°F	250°F
Oxidation	D-943	***Typically above 3000 hours***		
Dielectric Strength	D-877	***Typically above 35 kV***		

PACKAGING AVAILABLE

- Carton, 4/1 Gallons
- 5 Gallon Pail
- 55 Gallon Drum

HO-32

- L0770-057
- L0770-060
- L0770-062

HO-46

- L0771-057
- L0771-060
- L0771-062

PACKAGING AVAILABLE

- Carton, 4/1 Gallons
- 5 Gallon Pail
- 55 Gallon Drum

HO-68

- L0772-057
- L0772-060
- L0772-062