



ISO-9001 Registered Quality System.
ISO-21469 Compliant.

Sales, Service & Distribution Center

Newark, NJ 07105
Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center

Toledo, OH 43605
Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support

Phone: 1-800-733-4755

PRODUCT DATA

LUBRIPLATE MARINE & AUTO GUARD

DESCRIPTION

ONE PRODUCT TO SATISFY FOUR IMPORTANT CONSIDERATIONS:

- ⇒ Moisture Displacement
- ⇒ Rust Preventive Coating
- ⇒ Penetrating Fluid
- ⇒ Lubricant

APPLICATIONS & ADVANTAGES

Moisture Displacement

- ⇒ An excellent "wet start" product, featuring outstanding moisture displacement properties

Rust Preventive Coating

- ⇒ Possesses exceptional rust-proofing properties. Thirty-day test in humidity cabinet prove its rust-proofing properties. Light in viscosity, promotes rapid and complete draining.
- ⇒ Highly recommended for rust-proofing machine tool parts, steel cast parts, etc.

Penetrating Fluid

- ⇒ Exceptional penetration properties.
- ⇒ Recommended for nuts, bolts, valves, heat risers, cables, linkage, etc.

Lubricant

- ⇒ In addition to all the other properties, recommended for permanent and positive lubrication over a long period of time.
- ⇒ Aerosol package utilizes LUBRIPLATE'S SECURE STRAW DUAL SPRAY NOZZLE

Typical Test Data

PROPERTY	TEST METHOD	TYPICAL RESULTS*
Viscosity: SUS @ 100°F	ASTM D-2161	45
cSt @ 40°C	ASTM D-445	6
SUS @ 210°F	ASTM D-2161	31
cSt @ 100°C	ASTM D-445	1.5
Flash Point	ASTM D-92	280°F/138°C
Fire Point	ASTM D-92	305°F/152°C
Dielectric Strength	ASTM D-877 A	42 kV (average)
Color	ASTM D-1500	5
Appearance	Visual	Clear to Hazy

PACKAGING AVAILABLE

Carton, 4/1 Gallon Jugs
5 Gallon Pail
16 Gallon Drum
55 Gallon Drum
Carton 12/12 oz. Aerosol Cans

Part No.

L0717-057
L0717-060
L0717-061
L0717-062
L0774-063