



ISO-9001 Registered Quality System.
ISO-21469 Compliant.

Sales, Service & Distribution Center

Newark, NJ 07105
Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center

Toledo, OH 43605
Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support

Phone: 1-800-733-4755

PRODUCT DATA

LUBRIPLATE AIR TOOL LUBRICANT

DESCRIPTION

LUBRIPLATE Air Tool Lubricant is an air tool oil that provides excellent lubrication for both rotary and reciprocating types of air tools, such as chipping hammers, impact wrenches, air motors, grinders, reamers, drills, etc. It can be fed through an air line lubricator, or applied directly into the tool through the quick coupling air connection. LUBRIPLATE Air Tool Lubricant provides not only superior lubrication, but dissolves and prevents the formation of gum and varnish deposits so often associated with air tool operations.

APPLICATIONS

LUBRIPLATE Air Tool Lubricant, as an air line lubricant, has been used very effectively on the lift cylinders of can fillers in breweries, bottling plants and canning plants, keeping the cylinders clean and eliminating hand cleaning.

ADVANTAGES

For the utmost in safe, simple and economical lubrication of rotary and reciprocating types of air tools, small amounts of LUBRIPLATE Air Tool Lubricant, used daily, will effectively lubricate the air tool, keeping it clean and free-running.

Typical Test Data

PROPERTY	TEST METHOD	TYPICAL RESULTS*
Viscosity: SUS @ 100°F	ASTM D-2161	147
cSt @ 40°C	ASTM D-445	30
SUS @ 210°F	ASTM D-2161	44
cSt @ 100°C	ASTM D-445	5
Viscosity Index	ASTM D-2270	120
ISO Grade	ASTM D-2422	32
Flash Point	ASTM D-92	385°F/196°C
Aniline Point	ASTM D-611	200°F/93°C
API Gravity	ASTM D-287	27.4
Pour point	ASTM D-97	-30°F/-34°C

PACKAGING AVAILABLE

Carton 12/1 qt. Plastic Jugs
Carton 4/1 Gallon Jugs
16 oz. bottle with squirt nozzle
5 Gallon Pail
16 Gallon Drum
55 Gallon Drum

Part No.

L0713-054
L0713-057
L0713-026
L0713-060
L0713-061
L0713-062