



ISO-9001 Registered Quality System.  
ISO-21469 Compliant.

**Sales, Service & Distribution Center**  
Newark, NJ 07105  
Phone: 973-589-9150 Fax: 973-589-4432

**Manufacturing, Sales, Service & Distribution Center**  
Toledo, OH 43605  
Phone: 419-691-2491 Fax: 419-693-3806

**Sales and Tech Service Support**  
Phone: 1-800-733-4755

## PRODUCT DATA

# LUBRIPLATE PURE FLUSH

"This product is certified OU Kosher Pareve"  
"This product is Halal certified"

\*NSF International H-1 Registered  
NSF ISO21469 Certification

## DESCRIPTION

LUBRIPLATE Pure Flush is a lubricating, flushing and cleansing oil that can be used in food, beverage and pharmaceutical processing plants in any area where there is a possibility of exposure of the lubricated machinery part(s) to edible products.

LUBRIPLATE Pure Flush is a non-drying lubricating cleanser that can be used along with the existing lubricant to clean equipment of carbonaceous debris, sludge, dirt, etc., without dismantling machinery. This will save on labor costs, downtime, replacement parts, etc.

## APPLICATIONS

LUBRIPLATE Pure Flush can be used to clean and flush bearings, gear cases, hydraulic systems, centralized lubricating systems, chain and air lines/air tools.

## ADVANTAGES

While LUBRIPLATE Pure Flush has excellent cleaning capabilities and load-carrying properties, it should always be used along with the existing lubricant at recommended treat levels for flushing and cleansing.

## COMPATIBILITY

LUBRIPLATE Pure Flush is a petroleum hydrocarbon based product. It is fully compatible with other petroleum-based lubricants such as USP White Mineral Oil, Technical White Oil, Paraffinic or Naphthenic based mineral oils. LUBRIPLATE Pure Flush is also compatible with synthetic fluids, which are known to be compatible with petroleum-based products such as polyalphaolefin (PAO) based products. LUBRIPLATE Pure Flush is also compatible with seals and elastomers, which are known to be compatible with petroleum based lubricants. Please see instructional bulletin 8-20A for more details.

**(For any questions regarding compatibility, please contact LUBRIPLATE Technical Services.)**

## Typical Test Data

PROPERTY	TEST METHOD	TYPICAL RESULTS*
Viscosity SUS @ 100°F	ASTM D-2161	50
Viscosity SUS @ 210°F	ASTM D-2161	32
Viscosity cSt @ 40°C	ASTM D-445	10.5
Viscosity cSt @ 100°C	ASTM D-445	1.8
Flash Point	ASTM D-92	350°F/176°C
Fire Point	ASTM D-92	360°F/182°C
Pour Point	ASTM D-97	-35°F/-37°C
API Gravity	ASTM D-287	40.0
Color	ASTM D-1500	0.0
Aniline Point	ASTM D-611	220°F/104°C
Four Ball Wear Test	ASTM D-2266	0.60 mm

## PACKAGING AVAILABLE

Carton, 12/1 Quart Plastic  
Carton, 4/1 Gallon Jugs  
5 Gallon Pail  
55 Gallon Drum

## Part No.

L0816-054  
L0816-057  
L0816-060  
L0816-062

**\*NSF International H-1 Registration No.**  
(Meets former USDA 1998 Guidelines)

**126121**

\*Registered H-1 by NSF International for use in food processing facilities as a lubricant or anti-rust agent on equipment in which there may be incidental contact involving the lubricated part and the edible product.

"LUBRIPLATE PURE FLUSH contains no components derived from TSE/BSE relevant animal species; therefore, it is compliant with the requirements of the TSE Note for Guidance EMA/410/01 Rev. 3 July 2011."

Manufactured with ingredients that comply with FDA 21 CFR 178.357.

## STORAGE RECOMMENDATIONS

- ⇒ Products should be stored between 40°F-120°F
- ⇒ Products should be stored in a dry covered environment
- ⇒ Products should not be stored in warm, direct sunlight
- ⇒ Improper storage conditions can significantly alter the shelf life of the product. Such conditions would include temperature, moisture, open containers, etc.



Nonfood Compounds  
H1 Registered  
ISO 21469 Certified

PAREVE

HALAL