



ISO-9001 Registered Quality System.
ISO-21469 Compliant.

Sales, Service & Distribution Center

Newark, NJ 07105
Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center

Toledo, OH 43605
Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support

Phone: 1-800-733-4755

PRODUCT DATA

LUBRIPLATE DEXRON III/MERCON UNIVERSAL AUTOMATIC TRANSMISSION FLUID

DESCRIPTION

LUBRIPLATE Dexron III/Mercon is a premium fluid fully qualified to cover current requirements for both General Motors and Ford.

General Motors Qualification No. - F-30481
Ford Qualification No. - M940507

ADVANTAGES

- ⇒ Superior Wear Prevention
- ⇒ Extensive Oxidation Stability
- ⇒ All Season Protection
- ⇒ Rust and Corrosion Resistant
- ⇒ Foam Resistant
- ⇒ Excellent Compatibility with Seals & Metal Components
- ⇒ Controlled Frictional Properties
- ⇒ Thermal Stability

APPLICATIONS

Dexron III is a General Motors trademark for qualified automatic transmission fluids. Mercon covers all automatic transmissions for Ford model year 1988 and after. LUBRIPLATE Dexron III/Mercon is designated as make-up and/or refill fluids to meet respective car warranties.

RECOMMENDATIONS

LUBRIPLATE Dexron III/Mercon is also recommended for:

- ⇒ Allison C-4
- ⇒ Dexron II Fluids (Dexron IIE and Dexron IID)
- ⇒ Dexron Fluids
- ⇒ ATF Type "A" Suffix "A" Fluids
- ⇒ Ford M2C138CJ
- ⇒ Ford M2C166H

As well as Chrysler and American Motors cars, vans and light trucks plus those imported vehicles specifying Dexron II. This fluid can be used as a hydraulic fluid where specified by such manufacturers as Vickers and Sundstrand.

This product is not recommended to replace ATF Type "F" (ESE-M2C33F) or as a power steering fluid unless specified by the manufacturer.

Typical Test Data

PROPERTY	TEST METHOD	TYPICAL RESULTS*
Viscosity cSt @ 40°C	ASTM D-445	31 - 41
Viscosity cSt @ 100°C	ASTM D-445	6.9 - 7.9
Brookfield @ -40°C		17,600 cP
Viscosity Index	ASTM D-2270	190
API Gravity	ASTM D-287	31.2
Flash Point, °C (°F)	ASTM D-92	185 (365)
Pour Point, °C (°F)	ASTM D-5950	-40 (-40)
Color	ASTM D-2896	Red

PACKAGING AVAILABLE

Carton, 12/1 Quart Plastic Bottles
5 Gallon Pail
55 Gallon Drum

Part No.

L0867-054
L0867-060
L0867-062