



ISO-9001 Registered Quality System.  
ISO-21469 Compliant.

#### Sales, Service & Distribution Center

Newark, NJ 07105  
Phone: 973-589-9150 Fax: 973-589-4432

#### Manufacturing, Sales, Service & Distribution Center

Toledo, OH 43605  
Phone: 419-691-2491 Fax: 419-693-3806

#### Sales and Tech Service Support

Phone: 1-800-733-4755

## PRODUCT DATA

# LUBRIPLATE SUPER 345 MOTOR OIL SAE 5W-30

## DESCRIPTION

LUBRIPLATE Super 345 Motor Oil SAE 5W-30 is a superior-quality, high detergent automotive engine oil specially formulated with synthetic base stocks and mineral oil for better fuel economy and to reduce harmful emissions while meeting and exceeding the OEM's stringent lubrication requirements of today's engines.

LUBRIPLATE Super 345 Motor Oil SAE 5W-30 is formulated using an advanced additive package that provides maximum protection against wear, rust, corrosion, thermal breakdown, acid formation, reduces sludge build up and the formation of sludge and varnish deposits.

#### Meets or exceeds the following specifications:

- ⇒ API Service Category SN, SM, SL, SJ, SH, SG, SF, SE, SD, SC
- ⇒ Energy Conserving, ILSAC GF-5
- ⇒ Meets or exceeds the requirements of MIL-1-46152E
- ⇒ Ford WSS-M2C929-A (5W30)
- ⇒ DaimlerChrysler DC MS-639N, MS-6395L
- ⇒ GM 6094M specification (5W30), GM 9986231 (SAE 5W30)
- ⇒ Toyota service fill requirements for 5000-mile service intervals

## APPLICATIONS

LUBRIPLATE Super 345 Motor Oil SAE 5W-30 can be used in passenger cars, light trucks and sport utility vehicles under all operating conditions.

## ADVANTAGES

- ⇒ Friction-modified for improved fuel economy
- ⇒ Protects against sludge and varnish formation
- ⇒ Helps protect emissions system
- ⇒ Minimized rust and corrosion
- ⇒ Good low temperature pour point
- ⇒ Excellent resistance to viscosity and thermal breakdown at high temperatures

## Typical Test Data

PROPERTY	TEST METHOD	TYPICAL RESULTS
Viscosity cSt @ 100°C	ASTM D-445	10.5
6600 cP max @ Deg C		-35
SAE Grade		5W30
Viscosity Index	ASTM D-2270	155
Specific Gravity	ASTM D-4052	0.872
Flash Point, COC (°F)	ASTM D-92	400
Pour Point, °C (min)	ASTM D-5950	-35

## PACKAGING AVAILABLE

Carton, 12/1 Quart Plastic Bottles  
5 Gallon Pail  
55 Gallon Drum

## Part No.

L0732-054  
L0732-060  
L0732-062