



ISO-9001 Registered Quality System.
ISO-21469 Compliant.

Sales, Service & Distribution Center
Newark, NJ 07105
Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center
Toledo, OH 43605
Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support
Phone: 1-800-733-4755

PRODUCT DATA

LUBRIPLATE FG AIR TOOL LUBRICANT

"This product is certified OU Kosher Pareve"
"This product is Halal certified"

**NSF International H-1 Registered
NSF ISO21469 Certification*

DESCRIPTION

LUBRIPLATE FG Air Tool Lubricant is an air tool oil that provides excellent lubrication for both rotary and reciprocating types of air tools, such as chipping hammers, impact wrenches, air motors, grinders, reamers, drills, etc. It can be fed through an air line lubricator, or applied directly into the tool through the quick coupling air connection. LUBRIPLATE FG Air Tool Lubricant provides not only superior lubrication, but dissolves and prevents the formation of gum and varnish deposits so often associated with air tool operations.

APPLICATIONS

LUBRIPLATE FG Air Tool Lubricant, as an air line lubricant, has been used very effectively on the lift cylinders of can fillers in breweries, bottling plants and canning plants, keeping the cylinders clean and eliminating hand cleaning.

ADVANTAGES

For the utmost in safe, simple and economical lubrication of rotary and reciprocating types of air tools, small amounts of LUBRIPLATE FG Air Tool Lubricant, used daily, will effectively lubricate the air tool, keeping it clean and free-running.

STORAGE RECOMMENDATIONS

For the utmost in safe, simple and economical lubrication of rotary and reciprocating types of air tools, small amounts of LUBRIPLATE FG Air Tool Lubricant, used daily, will effectively lubricate the air tool, keeping it clean and free-running.

- ⇒ Products should be stored between 40°F-120°F
- ⇒ Products should be stored in a dry covered environment
- ⇒ Products should not be stored in warm, direct sunlight
- ⇒ Improper storage conditions can significantly alter the shelf life of the product. Such conditions would include temperature, moisture, open containers, etc.

Typical Test Data

PROPERTY	TEST METHOD	TYPICAL RESULTS*
Viscosity: SUS @ 100°F	ASTM D-2161	146
cSt @ 40°C	ASTM D-445	31
SUS @ 210°F	ASTM D-2161	44
cSt @ 100°C	ASTM D-445	5.4
Viscosity Index	ASTM D-2270	107
ISO Grade	ASTM D-2422	32
Flash Point	ASTM D-92	400°F/204°C
Aniline Point	ASTM D-611	215°F/102°C
API Gravity	ASTM D-287	30.5
Pour point	ASTM D-97	-20°F/-29°C

PACKAGING AVAILABLE

Part No.

Carton of 12 / 16 oz. Bottles	L0711-026
Carton of 4 / 1 Gallon Jugs	L0711-057
5 Gallon Pail	L0711-060
Quarter Drum	L0711-061
55 Gallon Drum	L0711-062

NSF International H1 Registration No.166390

