



ISO-9001 Registered Quality System.
ISO-21469 Compliant.

Sales, Service & Distribution Center

Newark, NJ 07105
Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center

Toledo, OH 43605
Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support

Phone: 1-800-733-4755

PRODUCT DATA

LUBRIPLATE SSO-FG 220

"These products are certified OU Kosher Pareve"

"These products are Halal certified"

*NSF International H-1 Registered
NSF ISO21469 Certification

DESCRIPTION

Engineered to meet the extreme requirements encountered in the food and beverage-processing industries such as water wash downs, steam, acidic conditions, etc., LUBRIPLATE SSO-FG 220 is formulated with premium performance additives and long-life synthetic base fluids that provide superior lubrication and outstanding oxidative, wear, rust and corrosion protection to the equipment. It is NSF H1 registered food grade.

APPLICATIONS

LUBRIPLATE SSO-FG 220 is a premium, fully synthetic lubricant designed to be used in seaming/canning equipment and related applications.

APPROVALS

- ⇒ Angelus Seamers
- ⇒ Zacmi Seamers

STORAGE RECOMMENDATIONS

- ⇒ Products should be stored between 40°F-120°F
- ⇒ Products should be stored in a dry covered environment
- ⇒ Products should not be stored in warm, direct sunlight
- ⇒ Improper storage conditions can significantly alter the shelf life of the product. Such conditions would include temperature, moisture, open containers, etc.

Typical Test Data

PROPERTY	TEST METHOD	TYPICAL RESULTS*
		SSO-FG-220
Appearance	Visual	Pale Yellow
ISO VG	ASTM D-2422	220
Viscosity:		
SUS @ 100°F	ASTM D-88	1,088
SUS @ 210°F	ASTM D-88	128
cSt @ 40°C	ASTM D-445	222
cSt @ 100°C	ASTM D-445	26
Viscosity Index	ASTM D-2270	146
Color	ASTM D-1500	1.0 Max
API Gravity	ASTM D-287	32.6
Specific Gravity	ASTM D-187	0.841
Pounds/Gallons		7.01
Flash Point °F	ASTM D-92	520
Fire Point °F	ASTM D-92	540
Pour Point °F	ASTM D-97	-42
TAN	ASTM D-974	0.3
Cu Corrosion	ASTM D-130A	1b
Four Ball Wear	ASTM D-4172	0.32 mm
Rust Prevention	ASTM D-665	Pass No Corrosion

PACKAGING AVAILABLE

SSO-FG-220

5 Gallon Pail	L0928-060
55 Gallon Drum	L0928-062
330 Gallon Disposable Bin	***

*NSF Int'l H-1 Registration No.'s 157613

(Meets former USDA 1998 Guidelines)

"The **LUBRIPLATE SSO-FG 220** contains no components derived from TSE/BSE relevant animal species; therefore, it is compliant with the requirements of the TSE Note for Guidance EMA/410/01 Rev. 3 July 2011".

*Registered H-1 by NSF International for use in food processing facilities as a lubricant or anti-rust agent on equipment in which there may be incidental contact involving the lubricated part and the edible product.



Nonfood Compounds
H1 Registered
ISO 21469 Certified



PAREVE



HALAL