



ISO-9001 Registered Quality System.  
ISO-21469 Compliant.

**Sales, Service & Distribution Center**

Newark, NJ 07105  
Phone: 973-589-9150 Fax: 973-589-4432

**Manufacturing, Sales, Service & Distribution Center**

Toledo, OH 43605  
Phone: 419-691-2491 Fax: 419-693-3806

**Sales and Tech Service Support**

Phone: 1-800-733-4755

**LUBRIPLATE "930" SERIES**

The LUBRIPLATE "930" Series of lubricants are also listed as "multipurpose" but with a higher operating temperature range than the "630" Series. These lubricants possess high film strength and exceptional resistance to water, steam and other adverse operating conditions. Since these lubricants are of the non-melt type, they can be used successfully for high temperature applications up to 375°F and for short intervals up to 400°F.

The LUBRIPLATE "930" Series of lubricants are shear stable multipurpose greases for both plain and anti-friction bearings. These lubricants are recommended wherever Microgel greases, Bentone greases, Urea greases and Complex greases are recommended and used.

LUBRIPLATE No. 930-AAA is an NLGI No. 0 consistency and is ideal and recommended for centralized lubricating systems. This lubricant is also a superior grease for certain types of enclosed gear cases of medium speed and no seals.

LUBRIPLATE NO. 930-AA is an NLGI No. 1 lubricant highly recommended for automatic grease dispensing devices and pressure gun applications. LUBRIPLATE No. 930-AA is available in the convenient 14½-ounce grease-gun cartridge.

LUBRIPLATE No. 930-A is a heavy-body NLGI No. 2.5 lubricant for applications requiring a heavy type product such as grease cups.

LUBRIPLATE No. 930-2 is an NLGI No. 2 lubricant for general grease-gun applications and is also available in the convenient 14½-ounce cartridge.

(Over)

**TYPICAL TESTS**

<b><u>LUBRIPLATE No.</u></b>	<b><u>930-AAA</u></b>	<b><u>930-AA</u></b>	<b><u>930-A</u></b>	<b><u>930-2</u></b>
Type of Thickener	Gelling Agent	Gelling Agent	Gelling Agent	Gelling Agent
NLGI No.	0	1	2.5	2
Worked Penetration Range @ 77°F	355/385	310/340	235/260	265/295
ASTM Dropping Point	Non-Melt Type	Non-Melt Type	Non-Melt Type	Non-Melt Type
Mineral Oil Viscosity				
SUS @ 100°F	900	750	750	750
cSt @ 40°C	167	135	135	135
Color	Off-White	Off-White	Off-White	Off-White

**PART NUMBERS**

<b><u>Packaging Available</u></b>	<b><u>930-AAA</u></b>	<b><u>930-AA</u></b>	<b><u>930-A</u></b>	<b><u>930-2</u></b>
Carton, 24/14 oz. Cans	L0098-001	L0096-001	L0095-001	-----
Carton, 6/6 lb. Cans	L0098-006	L0096-006	L0095-006	-----
35 lb. Pail	L0098-035	L0096-035	L0095-035	L0100-035
120 lb., Quarter Size, Drum	L0098-039	L0096-039	L0095-039	L0100-039
Full Size Drum	L0098-040	L0096-040	-----	L0100-040
Carton, 36/1¾ oz. Tubes (1x6)	-----	L0096-086	-----	-----
Carton, 40/14½ oz. Cartridges	-----	L0096-098	-----	L0100-098

Printed in USA  
Revised 4-15-08